



# Pyran Platinum L

20-180 Minute Premium Laminated Fire Protective Safety Ceramic

### Product Advantages

- The first premium-grade fire rated glass ceramic made specifically for architectural applications.
- Neutral coloration designed to more closely match float glass.
- Advanced manufacturing process eliminates the added cost of surface polishing.
- Environmentally-friendly glass ceramic manufactured free of toxins and hazardous heavy metals.
- Laminated glass ceramic meets the highest human impact safety requirements.
- Readily available through our factory direct Quick-Ship program and our nationwide distributor network.
- Insulated, obscured and other custom make-ups available.

### Specifications

- Thickness: 3/8" (9 mm)
- Weight: 4 lbs/sq. ft. (20 kg/m2)
- Appearance: Free of amber tint
- Impact Safety-Rated: CPSC 16 CFR 1201 Cat. I and II, ANSI Z97.1
- Hose-Stream Test: Pass
- Visible Light Transmittance: 73%
- STC Rating: 36 dB



### Pyran Platinum L General Characteristics

Fire Rating	Application	Max. CV Area	Max. CV Width	Max. CV Height	Stops
20-90 min.*	Sidelites Windows Transoms	3,143 sq. in. (2.03 m2)	75 in. (1.91 m)	75 in. (1.91 m)	5/8 in. (16 mm)
20-90 min.*	Doors (Non-Temp. Rise)	2,736 sq. in. (1.77 m2)	36 in. (0.91 m)	75 in. (1.91 m)	5/8 in. (16 mm)
Up to 180 min.	Doors (Temp. Rise)	100 sq. in. (0.06 m2)	12 in. (0.30 m)	33 in. (0.84 m)	1/2 in. (13 mm)